

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-288001

(43)Date of publication of application : 19.10.1999

(51)Int.Cl.

G02F 1/1345

(21)Application number : 10-088524

(71)Applicant : CITIZEN WATCH CO LTD

(22)Date of filing : 01.04.1998


(72)Inventor : SUGURO AKIRA

(54) LIQUID CRYSTAL DISPLAY DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To narrow the non-display regions by wiring patterns and to obtain a liquid panel of a narrow picture frame by using a semiconductor chip integrated with a common driver and a data driver and effectively utilizing a non-display region.

SOLUTION: A one chip driver 11 is a circuit integrated with the ordinary common driver and data driver. The one chip driver is packaged on a first substrate formed with scanning electrodes or a second substrate formed with data electrodes. The second substrate formed with the data electrodes or the first substrate formed with the scanning electrodes facing each other are connected by a conductive seal. The long sides of the one chip driver 11 are arranged at the center of the data electrodes in parallel with the scanning electrodes. The scanning electrode wiring patterns 17a are so arranged as to hold the data electrode wiring patterns 17b at the center. The scanning electrode wiring patterns 17a are so arranged as to pass right under the one chip driver 11. The wiring patterns are confined within the region of half the product of the conventional wiring pitches and the number of the scanning lines.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office